

Material Safety Data Sheet



Zep Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-793-7776

Section 1. Chemical Product and Company Identification

Product name Z-TREAD UTILITY FLOOR FINISH
Product use Floor Finish
Product code R043
Date of issue 08/07/08 **Supersedes**

Emergency Telephone Numbers

For MSDS Information:
Compliance Services 1-877-793-7776

For Medical Emergency
INFOTRAC: (877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By
Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

CAUTION !

CAUSES EYE IRRITATION.

*Hazard Determination System (HDS): Health, Flammability, Reactivity



NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Inhalation.

Eyes Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

Skin May cause skin irritation. Product may be dermal absorbed. Skin inflammation is characterized by itching, scaling, or reddening.

Inhalation Avoid inhalation of vapor, spray or mist. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

Ingestion May be harmful if swallowed. Can cause gastrointestinal disturbances.

Chronic effects

Contains material which may cause damage to the following organs: kidneys, liver, central nervous system (CNS).

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

2-(2-ETHOXYETHOXY)-ETHANOL; diethylene glycol monoethyl ether, ethoxydiglycol	111-90-0	1 - 10
DIPROPYLENE GLYCOL METHYL ETHER; dipropylene glycol monomethyl ether	34590-94-8	1 - 10

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

Skin Contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

Inhalation Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)

Flash Point None.

Flammable Limits Not available.

Flammability Non-combustible.

Fire hazard In a fire or if heated, a pressure increase will occur and the container may burst.

Fire-Fighting Procedures Use an extinguishing agent suitable for the surrounding fire.



Section 6. Accidental Release Measures

Spill Clean up Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Do not ingest. Do not reuse container. Observe label precautions. Wash thoroughly after handling.

Storage Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

DIPROPYLENE GLYCOL METHYL ETHER; dipropylene glycol monomethyl ether

Exposure limits

ACGIH TLV (United States, 2003). Skin
TWA: 100 ppm 8 hour(s).
STEL: 150 ppm 15 minute(s).
OSHA PEL (United States, 2003). Skin
TWA: 100 ppm 8 hour(s).

Personal Protective Equipment (PPE)

Eyes Safety glasses.



Body For prolonged or repeated handling, use the following type of gloves: Neoprene gloves. Nitrile gloves. Rubber gloves.

Respiratory Use with adequate ventilation. No special protection is required.

Section 9. Physical and Chemical Properties

Physical State Liquid.

Color Milky-white

pH 8.0 - 9.0

Odor Mild.

Boiling Point 100°C (212°F)

Vapor Pressure Not determined.

Specific Gravity 1.024

Vapor Density Not determined.

Solubility Easily soluble in the following materials: cold water and hot water.

Evaporation Rate 1 (Water = 1)

VOC (Consumer) 24.12 (g/l). 0.20 lbs/gal (2.36%)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Slightly reactive or incompatible with the following materials: oxidizing materials.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Diethylene Glycol Monoethyl Ether	LD50 Dermal	Rabbit	9143 mg/kg	-
	LD50 Oral	Rat	10502 mg/kg	-
	LD50 Oral	Mouse	6301 mg/kg	-
	LC50 Inhalation Vapor	Rat	>200 mg/L	1 hours
Dipropylene Glycol Methyl Ether	LD50 Dermal	Rabbit	13000 mg/kg	-
	LD50 Oral	Rat	5220 mg/kg	-

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste

Section 14. Transport Information

Regulatory information **UN number** **Proper shipping name** **Classes** **PG*** **Label**

DOT Classification	Not regulated.	Not a DOT controlled material (United States).			
IMDG Class	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

Product name

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: Diethylene Glycol Monoethyl Ether

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations**California Prop 65**

WARNING: This product contains a chemical or chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.:
Ethylene Glycol Monoethyl Ether

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.