

# Material Safety Data Sheet



Zep Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-793-7776

## Section 1. Chemical Product and Company Identification

**Product name** PARTS WASHER SOLVENT  
**Product use** Parts Cleaner Solvent  
**Product code** R198  
**Date of issue** 07/08/09 **Supersedes**

### Emergency Telephone Numbers

**For MSDS Information:**  
Compliance Services 1-877-793-7776

**For Medical Emergency**  
(877) 541-2016 Toll Free - All Calls Recorded

**For Transportation Emergency**  
CHEMTREC: (800) 424-9300 - All Calls Recorded  
In the District of Columbia (202) 483-7616

**Prepared By**  
Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

## Section 2. Hazards Identification

### Emergency overview

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

WARNING !



COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.  
HARMFUL IF SWALLOWED.

**NOTE:** MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

### Acute Effects

### Routes of Entry

Dermal contact. Inhalation.

**Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.

**Skin** May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.

**Inhalation** Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

**Ingestion** Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

**Chronic effects** Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

### Product/ingredient name

Not available.

**Additional Information: See Toxicological Information (Section 11)**

## Section 3. Composition/Information on Ingredients

LIGHT ALIPHATIC NAPHTHA; solvent naphtha (petroleum), medium aliphatics 64742-88-7 90 - 100

## Section 4. First Aid Measures

**Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.

**Skin Contact** Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.

**Inhalation** Move exposed person to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

**Ingestion** Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)



<b>Flash Point</b>	Closed cup: 61.667°C (143°F) [Pensky-Martens.]
<b>Flammable Limits</b>	Lower: 1% Upper: 7%
<b>Flammability</b>	Combustible liquid.
<b>Fire hazard</b>	Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
<b>Fire-Fighting Procedures</b>	Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.

**Section 6. Accidental Release Measures**

<b>Spill Clean up</b>	Eliminate all ignition sources. Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.
-----------------------	---

**Section 7. Handling and Storage**

<b>Handling</b>	Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Store and use away from heat, sparks, open flame or any other ignition source. Wash thoroughly after handling. Do not reuse container.
<b>Storage</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

LIGHT ALIPHATIC NAPHTHA; solvent naphtha (petroleum), medium aliphatics

**Exposure limits**


ACGIH TLV (United States).

TWA: 100 ppm 8 hour(s).

Supplier Suggested TLV (United States).

TWA: 100 ppm 8 hour(s).

**Personal Protective Equipment (PPE)**

<b>Eyes</b>	Safety glasses.	
<b>Body</b>	Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Rubber gloves. Nitrile gloves.	
<b>Respiratory</b>	Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.	

**Section 9. Physical and Chemical Properties**

<b>Physical State</b>	Liquid.	<b>Color</b>	Clear. Colorless.
<b>pH</b>	Not applicable	<b>Odor</b>	Solvent. [Slight]
<b>Boiling Point</b>	186.67°C (368°F)	<b>Vapor Pressure</b>	0.067 kPa (0.5 mm Hg)
<b>Specific Gravity</b>	0.79	<b>Vapor Density</b>	>1 [Air = 1]
<b>Solubility</b>	Insoluble in the following materials: cold water.	<b>Evaporation Rate</b>	0.14 (Butyl acetate. = 1)
		<b>VOC (Consumer)</b>	100% (789 g/L; 6.58 lbs/gal)

**Section 10. Stability and Reactivity**

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility</b>	Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous Polymerization</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	carbon oxides (CO, CO <sub>2</sub> )

**Section 11. Toxicological Information****Acute Toxicity**

Not available.

**Section 12. Ecological Information****Environmental Effects** No known significant effects or critical hazards.**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Non-hazardous waste**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>	Not regulated.	Not a DOT controlled material (United States).			
<b>IMDG Class</b>					

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>	Not regulated.	Not a DOT controlled material (United States).			
<b>IMDG Class</b>					

**NOTE:** DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

**Clean Water Act (CWA) 307:** No products were found.**Clean Water Act (CWA) 311:** No products were found.**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations****California Prop 65** No products were found.**Section 16. Other Information**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.