

Material Safety Data Sheet



Zep Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-793-7776

Section 1. Chemical Product and Company Identification

Product name VOC COMPLIANT SOLVENT
DEGREASER (AEROSOL)
Product use Aerosol Degreaser
Product code R202
Date of issue 07/20/09 **Supersedes**

Emergency Telephone Numbers

For MSDS Information:
Compliance Services 1-877-793-7776

For Medical Emergency
(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

DANGER !

*Hazard Determination System (HDS): Health, Flammability, Reactivity



FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire.
CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC
SKIN REACTION. VAPOR HARMFUL. CONTENTS UNDER
PRESSURE.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Dermal contact. Inhalation.

- Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.
- Skin** Causes skin irritation. May cause allergic reactions in certain individuals. May cause skin sensitization. Skin inflammation is characterized by itching, scaling, or reddening.
- Inhalation** Over-exposure by inhalation may cause respiratory irritation. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Can cause central nervous system (CNS) depression.
- Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Prolonged or repeated contact may dry skin and cause irritation. Contains material which may cause damage to the following organs: liver, central nervous system (CNS).

Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

HYDROTREATED LIGHT PETROLEUM DISTILLATES; paraffinic, naphthenic solvent	64742-47-8	60 - 70
D-LIMONENE; orange distillate; citrus terpene; cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)-	5989-27-5	15 - 25
DIPROPYLENE GLYCOL N-BUTYL ETHER; 1-(2-butoxy-1-methoxy)- 2-propanol; Glycol Ether DPNB	29911-28-2	5 - 15
CARBON DIOXIDE	124-38-9	1 - 5

Section 4. First Aid Measures

- Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
- Skin Contact** Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.
- Inhalation** Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point Not available.

Flammable Limits Not available.

Flammability FLAMMABLE. (CSMA)

Fire hazard FLAMMABLE LIQUID AND VAPOR. CONTENTS UNDER PRESSURE. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed.

Fire-Fighting Procedures Use an extinguishing agent suitable for the surrounding fire.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Empty containers retain product residue and can be hazardous. Wash thoroughly after handling.

Storage CONTENTS UNDER PRESSURE. Do not store above the following temperature: 49°C (120.2°F). Store in accordance with local regulations. Do not puncture or incinerate container. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection

Product name

HYDROTREATED LIGHT PETROLEUM DISTILLATES;
paraffinic, naphthenic solvent
CARBON DIOXIDE

Exposure limits

Supplier Suggested (United States).
TWA: 100 ppm 8 hour(s).
ACGIH TLV (United States).
TWA: 5000 ppm 8 hour(s).
STEL: 30000 ppm 15 minute(s).

Personal Protective Equipment (PPE)

Eyes Safety glasses.

Body Wear appropriate protective clothing to prevent skin contact.
Recommended: Neoprene gloves. Nitrile gloves.

Respiratory Avoid breathing vapors, spray or mists. Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.



Section 9. Physical and Chemical Properties

Physical State Liquid. [Aerosol.]

pH Not available.

Boiling Point 154°C (310°F)

Specific Gravity 0.828

Solubility Insoluble in the following materials: cold water and hot water.

Color Clear. Colorless.

Odor Citrus

Vapor Pressure Not determined.

Vapor Density Not determined.

Evaporation Rate Not determined.

VOC (Consumer) 34.6% 2.39 (lb/gal) 286 (g/l).

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials and alkalis.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products carbon oxides (CO, CO₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Hydrotreated Light Petroleum Distillates	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

Not available.

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D001
Classification: - [Hazardous waste.]
Origin: - [RCRA waste.]

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Consumer commodity	ORM-D	-	
IMDG Class					

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65 No products were found.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.