

Material Safety Data Sheet



Zep Inc.
1310 Seaboard Industrial Blvd.
Atlanta, GA 30318
1-877-793-7776

Section 1. Chemical Product and Company Identification

Product name CONCENTRATED SMOKE AND ODOR NEUTRALIZER
Product use Concentrated Liquid Odor Counteractant
Product code R239
Date of issue 11/02/09 **Supersedes**

Emergency Telephone Numbers

For MSDS Information:
Compliance Services 1-877-793-7776

For Medical Emergency
(877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
CHEMTREC: (800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Prepared By

Compliance Services
1420 Seaboard Industrial Blvd.
Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

WARNING!



FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.
MAY BE HARMFUL IF SWALLOWED.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects

Routes of Entry

Eye contact. Inhalation.

- Eyes** Causes eye irritation. Inflammation of the eye is characterized by redness, watering and itching.
- Skin** May cause skin irritation. Skin inflammation is characterized by itching, scaling, or reddening.
- Inhalation** Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation. Can cause dizziness, light-headedness, headache, nausea and blurred vision.
- Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

Chronic effects

Repeated or prolonged exposure to spray or mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Contains material which may cause damage to the following organs: kidneys, liver, central nervous system (CNS).

Carcinogenicity No known significant effects or critical hazards.

Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
C12-C16 ETHOXYLATED ALCOHOLS	68551-12-2	15 - 25
ETHANOL; ethyl alcohol; grain alcohol	64-17-5	15 - 25
HEXYLENE GLYCOL; 2-methyl-2,4-pentanediol; 2,4-dihydroxy-2-methylpentane; 1,2-hexanediol	107-41-5	5 - 15
DIPROPYLENE GLYCOL METHYL ETHER; dipropylene glycol monomethyl ether	34590-94-8	5 - 15
QUATERNARY AMMONIUM CHLORIDES; blend of alkyl dimethylbenzyl ammonium chlorides, alkyl dimethyl ethylbenzyl ammonium chlorides, and ethanol	85409-23-0; 68391-01-5	<3

Section 4. First Aid Measures

- Eye Contact** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin Contact** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops.
- Inhalation** Move exposed person to fresh air. If irritation persists, get medical attention.
- Ingestion** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



- Flash Point** Closed cup: 27.8°C (82°F)
[Tagliabue.]
- Flammable Limits** Lower: 2%
Upper: 12%
- Flammability** Flammable in the presence of open flames, sparks and static discharge.
- Fire hazard** Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
- Fire-Fighting Procedures** Use dry chemical, CO₂, water spray (fog) or foam.

Section 6. Accidental Release Measures

- Spill Clean up** Eliminate all ignition sources. Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and Storage

- Handling** Put on appropriate personal protective equipment (see section 8). Store and use away from heat, sparks, open flame or any other ignition source. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wash thoroughly after handling. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

ETHANOL; ethyl alcohol; grain alcohol

HEXYLENE GLYCOL; 2-methyl-2,4-pentanediol; 2,4-dihydroxy-2-methylpentane; 1,2-hexanediol

DIPROPYLENE GLYCOL METHYL ETHER; dipropylene glycol monomethyl ether

Exposure limits**ACGIH TLV / OSHA PEL (United States).**

TWA: 1000 ppm 8 hour(s).

OSHA / ACGIH (United States).

CEIL: 25 ppm

ACGIH TLV (United States, 2003). Absorbed through skin.



TWA: 100 ppm 8 hour(s).

STEL: 150 ppm 15 minute(s).

OSHA PEL (United States, 2003). Absorbed through skin.

TWA: 100 ppm 8 hour(s).

Personal Protective Equipment (PPE)

- Eyes** Safety glasses. 
- Body** Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves. 
- Respiratory** Avoid direct inhalation of spray. Use with adequate ventilation. A respirator is not needed under normal and intended conditions of product use.

Section 9. Physical and Chemical Properties

Physical State	Liquid.	Color	Colorless.
pH	8 to 9	Odor	Pleasant.
Boiling Point	85°C (185°F)	Vapor Pressure	Not determined.
Specific Gravity	0.97	Vapor Density	Not determined.
Solubility	Soluble in the following materials: cold water and hot water.	Evaporation Rate	1 (Water = 1)
		VOC (Consumer)	382.49 (g/l). 3.19 lbs/gal (39.50%)

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Incompatibility	Keep away from heat, sparks and flame. Reactive or incompatible with the following materials: oxidizing materials.
Hazardous Polymerization	Under normal conditions of storage and use, hazardous polymerization will not occur.
Hazardous Decomposition Products	carbon oxides (CO, CO ₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
C12-C16 Ethoxylated alcohols	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1380 mg/kg	-
Ethanol	LD50 Oral	Rat	7060 mg/kg	-
	LC50 Inhalation Vapor	Rat	20000 mg/m ³	4 hours
Hexylene Glycol	LD50 Dermal	Rabbit	12000 mg/kg	-
	LD50 Oral	Rat	3700 mg/kg	-
Dipropylene Glycol Methyl Ether	LD50 Dermal	Rabbit	13000 mg/kg	-
	LD50 Oral	Rat	5220 mg/kg	-
Quaternary Ammonium Chlorides	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>500 mg/kg	-

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
Quaternary Ammonium Chlorides	-	Acute EC50 0.058 mg/L	Daphnia	48 hours
	-	Acute LC50 0.52 mg/L	Fish - Bluegill.	96 hours

Section 13. Disposal Considerations**Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Non-hazardous waste

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	None.	-	-	
IMDG Class	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information**U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

[All Components of this product are listed or exempt from listing on TSCA Inventory.](#)

State Regulations

California Prop 65 No products were found.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.